



## Insulated Wire End Ferrules

for cables with thicker insulation (tri-rated cables)

Nominal size	Colour range			Dimensions (mm) (tolerances according to DIN 46228 part 4)					
	I(T)	II(W)	III(D)	$d_1$	$d_2$	$l_1$	$l_2$	$s_1$	$s_2$
EGB 0,5-8	WH	OG	WH	1,0	2,9	14,0	8,0	0,15	0,25
EGB 0,5-10	WH	OG	WH	1,0	2,9	16,0	10,0	0,15	0,25
EGB 0,75-8	BU	WH	GY	1,2	3,3	14,0	8,0	0,15	0,30
EGB 0,75-10	BU	WH	GY	1,2	3,3	16,0	10,0	0,15	0,30
EGB 1-8	RD	YE	RD	1,4	3,3	14,0	8,0	0,15	0,30
EGB 1-10	RD	YE	RD	1,4	3,3	16,0	10,0	0,15	0,30
EGB 1,5-8	BK	RD	BK	1,7	3,7	14,0	8,0	0,15	0,30
EGB 1,5-10	BK	RD	BK	1,7	3,7	16,0	10,0	0,15	0,30
EGB 2,5-8	GY	BU	BU	2,2	4,7	16,0	8,0	0,15	0,30
EGB 2,5-12	GY	BU	BU	2,2	4,7	20,0	12,0	0,15	0,30
EGB 16-12	WH	GN	BU	5,8	9,4	23,0	12,0	0,20	0,45
EGB 16-18	WH	GN	BU	5,8	9,4	29,0	18,0	0,20	0,45

Edit